



## NimbeLink 4G LTE-M (CAT M1), NB-IoT (NB1, NB2)

Airgain, a global leader in embedded cellular modem technology and asset tracking solutions, has introduced the NimbeLink NL-SW-LTE-QBG95 modem. This new NimbeLink modem offers LTE-M (CAT M1) and NB-IoT (NB1, NB2) connectivity for global applications with fallback to 2G, at lower power than the BG96 processor. It utilizes the Qualcomm 9205 chipset and Quectel BG95-M3 module. The modem also includes an integrated GPS/GNSS radio. The NL-SW-LTE-QBG95 is compatible with many of the world's LTE-M and NB-IoT networks.

NimbeLink cellular modems are designed to make cellular integration fast and easy. Exceptionally small, lowest power, and end-device certified, NimbeLink modems enable developers to quickly and reliably connect IoT products to cellular networks around the world. NimbeLink modems are backed by industry leading documentation and expert-level product support.

### FEATURES

- No carrier certification required
- Small form-factor
- NimbeLink Standard Interface
- Flexible antenna options
- USB & UART serial interfaces
- Verizon soldered down SIM and Micro-SIM 3FF slot
- Supports Power Save Mode and eDRX
- RoHS compliant/Radio Equipment Directive

### ADVANTAGES

- Global LTE coverage with 2G fallback
- Pin compatible with all NimbeLink modems
- GNSS support for GPS, GLONASS, Beidou, Galileo, QZSS
- Global hardware compatibility
- Dual SIM support

### PART NUMBER

	DESCRIPTION
NL-SW-LTE-QBG95	LTE-M, NB1, NB2, 2G fallback, with GNSS

## TECHNICAL SPECIFICATIONS

### TARGET REGION

Global

Compatible Carriers AT&T, Orange, Telstra, Telus, T-Mobile, Verizon, Vodafone, and more

### CELLULAR TECHNOLOGY

LTE Category LTE-M (CAT M1), NB-IoT (NB1, NB2)

LTE Frequency Bands LTE-FDD: B1[2100], B2[1900], B3[1800], B4[1700], B5[850], B8[900], B12[700], B13[700], B14[700], B17[700], B18[850], B19[850], B20[800], B25[1900], B26[850], B27[850], B28[700], B31[450], B66[1700], B71[600]

3G Technology Supported N/A

3G Frequency Band N/A

2G Technology Supported GSM, EDGE, GPRS

2G Frequency Band GSM850, EGSM900, DCS1800, PCS1900

### DATA SPEEDS

Download Rate and Upload Rate  
Download Max: LTE-M: 589 Kbps | NB-IoT: 136 Kbps | GPRS: 107 Kbps | EDGE: 296 Kbps  
Upload Max: LTE-M: 1.2 Mbps | NB-IoT: 150 Kbps | GPRS: 85.6 Kbps | EDGE: 236.8 Kbps

### HARDWARE

Form Factor NimbeLink Interface

Dimensions 29mm x 33mm x 10.5mm

Weight 8 grams

### INTERNET PROTOCOLS

Network Stack Support Integrated TCP/IP, UDP/IP, HTTP/HTTPS, FTP/SFTP, SSL/TLS, IPv4/IPv6, NITZ, PING, MQTT, PPP

SMS SMS supported

### LOCATION

GNSS GPS, GLONASS, Beidou, Galileo

### POWER SUPPLY

Supply Voltage 3.4V to 4.8V (3.8V nominal)

I/O Voltage 1.65V - 5.5V

Current Consumption	Average TBD mA   Peak TBD mA   Idle TBD mA   Sleep TBD uA
---------------------	---

## INTERFACES

Type	UART, USB (USB 2.0 compliant)
USB Driver Support	OS: Windows 7/8/10, Windows CE 5/6/7, Linux 2.6/3.X/4.1-4.14, Android 4/5/6/7/8 Drivers: PPP   QMI   AT Console   RIL Driver
RF	Primary, SISO DL (U.FL)

## SIM

Type	Integrated Verizon SIM, additional 3FF SIM slot
------	---

## APPROVALS

Regulatory Certifications	PTCRB, CE/RED (In-Progress), FCC, IC
Carrier	AT&T, Rogers, Telus, Verizon, and more
Compliance	RoHS compliant

## TEMPERATURE RANGE

Industrial Grade	-40°C to +85°C
------------------	----------------

## SUPPORT AND WARRANTY

1 Year standard warranty
--------------------------

## PATENTS

US 9,838,066
US 9,497,570
US D731,491